



3054C

Specifications

	3054C	3054E
Bore x Stroke	105 x 127 mm (4.1 x 5 in)	105 x 127 mm (4.1 x 5 in)
Displacement	4.4 liters (269 cu. in.)	4.4 liters (269 cu. in.)
Ship Weight (NA)	295 kg (650 lbs)	295 kg (650 lbs)
Approximate Dimensions:		
Length	663 mm (26.1 in)	663 mm (26.1 in)
Width	563 mm (22.2 in) (NA)	563 mm (22.2 in) (NA)
Height	775 mm (30.5 in) (NA)	775 mm (30.5 in) (NA)

3054C Ratings In-Line 4

C Rating (Intermittent)			C Rating (Intermittent)			C Rating (Intermittent)		
bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
NA			T			TA		
50	67	2200	60	80	2200	78.5	105	2400
54	72	2200	64.5	86	2200	83.5	112	2200
62	83	2400	72.5	97	2200	87	117	2200
60	80	2200	72.5	97	2400	95	127	2200

3054E Ratings In-Line 4

C Rating (Intermittent)			C Rating (Intermittent)			C Rating (Intermittent)		
bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
NA			T			TA		
64	86	2400	86	115	2500	97	130	2200

Features

- Cross flow cylinder head
- New gear train
- New balancer train
- Integrated closed circuit breaker
- Electric lift pump
- Open top deck block
- Integral oil cooler
- Choice of mechanical or electronic FIE

Benefits

- Horsepower and torque capabilities optimized
- Convenient installation
- Fuel timing control
- Lower fuel cost
- 500-hour service intervals
- Single-side servicing

Abbreviations used:

- NA**.....Naturally Aspirated
- T**.....Turbocharged
- TA**.....Turbocharged/Aftercooled
- E**.....Electronic

EPA Certified

Meets Tier 2, Stage II emissions requirements. Tier 2 refers to EPA (U.S.) requirements. Stage II refers to European requirements.