


C1.1



Specifications

	C0.5	C0.7
Bore x Stroke	67 x 72 mm (2.6 x 2.8 in.)	67 x 72 mm (2.6 x 2.8 in.)
Displacement	0.5 liters (31 cu. in.)	0.7 liters (46.5 cu. in.)
Ship Weight (NA)	62 kg (137 lbs)	76 kg (168 lbs)
Approximate Dimensions:		
Length	407 mm (16 in.)	442 mm (17.4 in.)
Width	371 mm (14.6 in.)	376 mm (14.8 in.)
Height	523 mm (20.6 in.)	536 mm (21.2 in.)

	C1.1	C1.5
Bore x Stroke	77 x 81 mm (3.0 x 3.2 in.)	84 x 90 mm (3.3 x 3.5 in.)
Displacement	1.1 liters (69 cu. in.)	1.5 liters (92 cu. in.)
Ship Weight (NA)	87 kg (191 lbs)	149 kg (329 lbs)
Approximate Dimensions:		
Length	496 mm (19.5 in.)	533 mm (21.0 in.)
Width	400 mm (15.7 in.)	427 mm (16.8 in.)
Height	578 mm (22.6 in.)	621 mm (24.5 in.)

C0.5 Ratings In-Line 2

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	8.2-10.2	11.0-13.7	2800-3600

C0.7 Ratings In-Line 3

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	12.2-15.3	16.3-20.5	2800-3600

C1.1 Ratings In-Line 3

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	17.4	23.3	3600
	18.4	24.7	2800
	19.1	25.6	3600
	19.5	26.1	3000
	21.0	28.1	3400

C1.5 Ratings In-Line 4

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	20.7	27.8	2200
	22.3	29.9	2400
	23.4	31.4	2600
	24.4	32.7	2800
	25.1	33.7	3000

Features

- Compact timing device for injection pump
- Closed circuit breather
- Improved governing system
- Optimized injectors
- Small installation package

Benefits

- Increase of horsepower and torque capabilities by 10%
- Quieter 3 db(A) noise reduction
- 500-hour service intervals
- Single-side servicing

Abbreviations used:

NA.....Naturally Aspirated

EPA Certified

Meets Tier 2, Stage II emissions requirements. Tier 2 refers to EPA (U.S.) requirements. Stage II refers to European requirements.